

## Tiger Claw TC-G GROOVED BOARD FASTENER



### PRODUCT DESCRIPTIONS

300 Series Heavy Gauge Stainless Steel Hidden Deck Fastener with black oxide coating.

### PRODUCT REQUIREMENTS

When using Tiger Claw fasteners please review and comply with these requirements to obtain proper installation. Failure to follow these requirements may result in deck failure and/or void of warranty.

Inspect decking material prior to installation. Omit any planks that contain hooks, twists, splits, cracks, or other defects. Always install decking with the crown upward.

#### When using:

Recommended for use in 5/4" or thicker decking. If using pre-grooved decking be sure that the groove is the correct dimension and location on the board so that it is compatible with the TC-G fastener. A router or biscuit joiner can be used to create grooves in solid edge decking.

### PRODUCT FEATURES & COMPATIBILITY

TC-G is ideal for composites and hardwoods\*, 5/4" to 2" in harsh or coastal environments.

#### **TC-G will work in the following decking lumber varieties:**

- Brazilian redwood
- Ipe
- Iron Wood
- Mangaris
- PurpleHeart
- Teak
- Cambara
- Meranti
- Medium Density Mahogany
- Atlantic White Cedar
- Cedar
- Eastern Spruce
- Eastern White Cedar
- Port Orford Cedar
- Western Red Cedar
- Western Redwood
- Yellow Cedar
- Boardwalk
- ChoiceDek
- Elements
- EverGrain
- EverX
- Fiberon
- Latitude

- Monarch
- Nexwood
- Portico
- Rhino Deck
- TimberTech (5/4 planking)
- Trex
- UltraDeck solid
- Veranda
- Weather Best
- WeatherShield
- Elk
- Endure
- Moisture shield
- Symmatrix

Please consult your manufacturer or ask us first if you plan to use any other decking material not listed above in your decking project.

**Unfortunately, due to the properties of the following materials, we do not recommend our fasteners for:**

- Pressure Treated Pine
- Decking Material prone to high shrinkage
- Hollow Composite decking
- Decking boards less than 7/8" thick

Product images and technical data courtesy of Tiger Claw